

PowerWAVE 9000DPA

(30–50 kVA)

Parallelable up to 1.5 MVA

Technical Specification



PowerWAVE 9000DPA

General data

System power range	30–1500 kVA
Max power per module	30 kVA / 40 kVA / 50 kVA
Max power per frame	250 kVA
Number of UPS modules in each frame	1 to 5
Weight (with modules/without batteries)	421–439 kg
Dimensions (mm) W x D x H	730 x 1975 x 800
Topology	Online double conversion
Parallel configuration	Up to 30 modules
UPS type	Modular (Decentralised Parallel Architecture)

Input

Nominal input voltage	3 x 380 / 220 V + N, 3 x 400 / 230 V + N, 3 x 415 / 240 V + N
Voltage tolerance (referred to 3 x 400 / 230 V)	For loads <100% (-25%, +15%), <80% (-30%, +15%), <60% (-40%, +15%)
Input distortion THDi	<3% @ 100% load
Frequency	30–70 Hz
Power factor @ 100% load	0.99

Output

Output power factor	0.8
Rated output voltage	3 x 380 / 220 V + N, 3 x 400 / 230 V + N, 3 x 415 / 240 V + N
Voltage distortion (referred to 3 x 400 / 230 V)	<±2% with linear load
Frequency	50 Hz or 60 Hz
Overload capability	1 min.: up to 150% / 10 min.: up to 125%
Unbalanced load	100% (all three phases regulated independently)
Crest factor	3 : 1 (load supported)

Efficiency

Overall efficiency	Up to 95.5%
In eco-mode configuration	99%

Environment

Storage temperature	-25°C to +70°C
Operating temperature	0°C to +40°C
Altitude	1000 m without derating

Battery

Battery capacity	Configurable up to several hours
Internal batteries	240 x 7/9 Ah (150 frame) / External batteries only (250 frame)

Communications

LCD	Yes (per module)
LEDs	LED for notification and alarm
Communication ports U	SB, RS-232, SNMP slot, potential-free contacts

Standards

Safety	IEC / EN 62040-1
Electromagnetic compatibility (EMC)	IEC / EN 62040-2
Performance	IEC / EN 62040-3
Manufacturing	ISO 9001, ISO 14001, OHSAS18001
Product certification	CE
IP rating	IP 20



INVESTORS
IN PEOPLE

Accredited
Until 2021



Constructionline
Gold Member



Accredited Contractor
CHAS.co.uk

KOHLER POWER
uninterruptible

Woodgate, Bartley Wood Business Park,
Hook, Hampshire RG27 9XA

Tel: 01256 386700

Fax: 01256 386701

Email: uksales.ups@kohler.com

www.kohler-ups.co.uk