

MINIpowerPLUS

(1.25–10 kVA)

Technical Specification



MINIpowerPLUS

All models

Input									
Input voltage (nominal)	230 V								
Input frequency	50/60 Hz \pm 2% autosensing								
Input voltage range	184 to 264 V at 100% load, 100 to 264 V at 50% load								
Input power factor	>0.99 at 20% load								
Input current total harmonic distortion	<3%								
Output voltage	230 V \pm 1%								
Output frequency	50/60 Hz synchronised								
Overload capacity									
Online modes	150% for 30s, 200% for 5s, 300% for 1s								
Battery modes	160% for 15s								
Protection degree	IP 21								
Standards	EN62040-1, EN50091-2, EN62040-3								
Batteries	3 x 12 V 9 Ah sealed lead-acid, maintenance-free batteries per board (standard) Up to several hours available on request								
MINIpowerPLUS tower	5000				10000				
Rated power (kVA)	1.25	2.5	3.75	5	5	6.25	7.5	8.75	10
Active power (kW)	0.875	1.75	2.625	3.5	3.5	4.375	5.25	6.125	7
Dimensions (mm) W x D x H	270 x 475 x 570				270 x 475 x 570				
Weight (kgs)	23.5	34	43	53	24	26.5	29	31.5	34
Battery	Internal (external optional)				External (additional cabinets)				
MINIpowerPLUS rack	5000								
Rated power (kVA)	1.25	2.5	3.75	5					
Active power (kW)	0.875	1.75	2.625	3.5					
Dimensions (mm) W x D x H	485.5 x 600 x 266		(6 U)						
Weight (kgs)	23.5	34	43	53					
Battery	Internal (external optional)								



INVESTORS
IN PEOPLE

Accredited
Until 2021



Constructionline
Gold Member



Accredited Contractor
CHAS.co.uk

KOHLER POWER
uninterruptible

Woodgate, Bartley Wood Business Park,
Hook, Hampshire RG27 9XA

Tel: 01256 386700

Fax: 01256 386701

Email: uksales.ups@kohler.com

www.kohler-ups.co.uk