


PowerWAVE 1000 (6-10 kVA)

Technical Specification



PowerWAVE 1000 (6–10 kVA)

Model	6 kVA	10 kVA
Input		
Voltage	176–280 VAC – line to neutral @ 100% load	
Frequency	45–70 Hz	
Phase	Single phase	
Power factor	≥0.99 @ 100% linear load	
Output		
Voltage distortion (THD)	≤2% @ 100% linear load, ≤7% @ run linear load with CF:25	
Voltage	200/208/220/230/240 vac selectable	
Voltage regulation	+/-1% (until low battery warning)	
Capacity	6000 VA/6000 W	10000 VA/10000 W
Rated power factor	1.0	
Wave form	Pure sine wave	
Transfer time inverter to bypass	0 ms	
Crest factor	3:1	
Efficiency (mains operation)	93%	94%
Efficiency (AC to AC, ECO)	98%	98%
External battery cabinet		
Type	Sealed lead acid maintenance free	
Capacity	12 V/9 AH	
No. of battery blocks per cabinet	20 pcs (connected or a single battery string)	
Display		
Readings on LCD	Input voltage, input frequency, output voltage, output frequency, load percentage, battery voltage, and inner temperature	
Self-diagnostics	Upon power-on and front panel setting	
Alarms		
Audible	Battery mode, battery low, overload, general error	
Protection		
Overload	Inverter supply: sliding scale: 105% continuous operation, 150% 160 ms, >150% switch to bypass	
Physical		
Dimensions (mm) W x D x H without battery	440 x 680 x 88	440 x 680 x 132
Input/output connection	Hardwire	
External battery connection	Plug-in and play	
Net weight (kg)	24	45
Environment		
Operating temperature	0°C – 40°C	
Altitude	0–1000 m without derating	
Humidity	20–95% non-condensing	
Environment – heat dissipation (approx)	<450 W	<650 W
Noise at 1 metre	≤55 dBA	
Computer interface		
Interface type	Standard RS232/EPO interface/USB	
Communication slots	2nd RS232, USB, relay contact, SNMP/WEB card	

Continued

Safety conformance

Quality assurance	ISO 9001:2000
Safety standard	EN62040-1-1, UL1778
EMC standard	EN 62040-2, EN 61000-3-2, EN61000 -3-3 FCC Part 15 class A
Certification protection class	CE (1P/1P), CTUVus (3P/1P)
Protection class	IP20

Battery bank

Model	Battery type	Maximum quantity	With batteries (Kg)	Dimension (W x H x D) mm
PWBAT-9-20	9AH	20 pcs	65.4	440 x 132 x 680 (3u)



INVESTORS
IN PEOPLE

Accredited
Until 2021



Constructionline
Gold Member



Accredited Contractor
CHAS.co.uk

KOHLER POWER
uninterruptible

Woodgate, Bartley Wood Business Park,
Hook, Hampshire RG27 9XA

Tel: 01256 386700

Fax: 01256 386701

Email: uksales.ups@kohler.com

www.kohler-ups.co.uk